

Run 2 Shifts On 1 Charge. Guaranteed.

	Family	Capacity (lbs)	Model	V
Class I	3-wheel counterbalanced	3,100	EFG 216	48 V
		3,490	EFG 218	48 V
		3,880	EFG 220	48 V
	4-wheel counterbalanced	4,960	EFG 425	80 V
		5,970	EFG 430	80V
	6,610	EFG 530	80 V	
	Stand-up counterbalanced	4,000	ETG 318	36 V
Class II	Pantograph single reach trucks	3,000	ETR 214	36 V
		3,500	ETR 216	36 V
		4,000	ETR 318	36 V
		4,500	ETR 320	36 V
		4,500	ETR 420	36V
	Pantograph deep reach trucks	3,500	ETR 316d	36 V
		3,500	ETR 416d	36 V
	Mid- / high-level order picker	2,200	EKS 412s	48 V
		3,000	EKS 414s	48 V
		3,000	EKS 314	36 V
	High-rack turret truck / order picker (man-up)	3,000	EKX 514	80 V
		3,500	EKX 516k	80 V
3,500		EKX 516	80 V	



Note: Equipping this model (these models) with a power source (e.g. Lithium-ion, Hydrogen Fuel cell, etc.) that has not been previously approved by the factory is considered a modification. Per OSHA 1910.178 and ANSI/ITSDF B56.1, please consult with your factory representative prior to installing any non-OEM power source that has not been previously approved.

1-877-JH-FORKS
www.logisnextamericas.com/jungheinrich



JFCB0310-16 04/2025 © 2025 Jungheinrich. All rights reserved. All registered trademarks are the property of their respective owners. Some products may be shown with optional equipment.



Complete Product Range



**Who Is Jungheinrich®?
Your Trusted Partner For
More Than 60 Years.**

Jungheinrich® is the world's leading brand of electric lift trucks. While others are new to electric, our 5th generation technology and more than 60 years of electric lift truck design allow us to deliver longer run times – up to two shifts on one charge – for greater productivity. Plus, we deliver a very low cost of ownership and operator-focused ergonomics that are truly second to none.

Strong Local Service And Support

- 340+ experienced dealers throughout the US, Canada and Mexico
- 24-hour parts delivery guarantee
- 5 parts distribution warehouses across the US
- Over 236,000 parts stocked locally
- Industry-leading run times

Innovative Warehouse Products.

Automated Guided Vehicles

Your benefits:

- Customization to your tasks and environment
- Simple integration into existing processes and systems
- High safety levels thanks to a comprehensive vehicle safety system
- Reliable transport with precise navigation
- High flexibility concerning layout changes
- No damage to transported goods and peripherals thanks to extensive safety sensors



Li 24
((●))

Pallet truck
ERE 225a
Capacity: 5,500 lbs.

Li 24
((●))

Tow tractor
EZS 350a
Towing capacity:
up to 11,000 lbs.

Li 24
((●))

Cantilevered truck
EKS 215a
Lift height: up to 236 inches
Capacity: 3,300 lbs.



Li 80
((●))

Turret truck
EKX 516ka / 516a
Capacity: 3,500 lbs.

Key

2/1 = Includes 2 Shifts
On 1 Charge
Guarantee models

Li = Lithium-ion
battery options
available

((●)) = Automated
Guided Vehicle

Counterbalanced



Li 48
2/1

48V 3 / 4-wheel
EFG B (A113-115 / C325(k)-330)
max. fork height: 256 inches
capacity: 2,500–6,000 lbs.



Li 48
2/1

36 / 48V 3-wheel
EFG 213 – 220
max. fork height: 275 inches
capacity: 2,500–4,000 lbs.



Li 48

36 / 48V 4-wheel
EFG 316k – 320
max. fork height: 275 inches
capacity: 3,000–4,000 lbs.



Li 80
2/1

80V 4-wheel
EFG 425k – 435
max. fork height: 295 inches
capacity: 5,000–7,000 lbs.



Li 80

80V 4-wheel
EFG 535k – 550
max. fork height: 295 inches
capacity: 7,000–11,000 lbs.



Li 36
2/1

36V stand-up counterbalanced
ETG 214 – 318
max. fork height: 276 inches
capacity: 3,000–4,000 lbs.



Li 48

36 / 48 V 4-Wheel Cushion
EFG C15 – C18L
max. fork height: 217 inches
capacity: 3,000–4,000 lbs.



Li 48

36 / 48 V 4-Wheel Cushion
EFG C23 – C30L
max. fork height: 276.4 inches
capacity: 4,500–6,500 lbs.

Order Pickers



24V low-level order picker
EKS 110
max. fork height: 110 inches
picking height: up to 181 inches
capacity: 2,200 lbs.



Li 24

24V medium-level order picker
EKS 210
max. fork height: 187 inches
picking height: up to 257 inches
capacity: 2,200 lbs.



Li 48
2/1

48V high-level order picker
EKS 412s / 414s
max. fork height: 492 inches
picking height: up to 563 inches
capacity: 2,200 / 3,000 lbs.



Li 36
2/1

24 / 36V mid- / high-level order picker
EKS 314
max. fork height: 366 inches
capacity: 3,000 lbs.

Other Narrow Aisle



24V low-lift pallet truck
ESE 220/320
travel distance: medium / long
capacity: 4,400 lbs.



24V small parts order picker
EKM 202
maximum standing/picking platform
height: 130 / 173 inches
maximum picking height: 208 inches
capacity: 474 lbs.

Moving Mast Reach



Li 48

48V sit-down moving mast reach truck
ETV 210/212/214/216 | ETM 214/216
max. fork height: 421 inches
capacity: 2,200 – 3,500 lbs.



Li 48

48V sit-down moving mast reach truck
ETV 318/320/325, ETM 325
max. fork height: 551 inches
capacity: 3,900–5,500 lbs.



Li 48

48V sit-down moving mast reach truck –
solid pneumatic tires
ETV C16/C20
max. fork height: 291 inches
capacity: 3,500 / 4,400 lbs.



Li 48

48V multi-directional sit-down
moving mast reach truck
ETV Q20/Q25
max. fork height: 421 inches
capacity: 4,400 / 5,500 lbs.

Turret Trucks



48V turret truck (man-down)
EFX 411 – 414
max. fork height: 354 inches
capacity: 2,400–3,000 lbs.



48V high-rack turret truck (man-up)
EKX 410/412
max. combined fork height: 452 inches
capacity: 2,200 / 2,600 lbs.



Li 80
2/1

80V high-rack turret truck (man-up)
EKX 514/516k/516
max. combined fork height: 689 inches
capacity: 3,000 / 3,500 lbs.

Tow Tractors



Li 24
350NA
only

24V tow tractor
EZS 350NA/C40NA
towing capacity: 11,000 / 8,800 lbs.



Li 48

48V sit-down tow tractor
EZS 570NA/580NA/590NA
towing capacity: 15,400 /
17,600 / 19,800 lbs.



80V sit-down tow tractor
EZS 7280NA/7280XL
towing capacity: 61,700 lbs.

Pallet Movers



Li 24

24V walkie pallet truck
EJE 120/225
travel distance: short
capacity: 4,500 / 6,000 lbs.



Li 24

24V light-duty walkie pallet truck
AME 15
travel distance: short
capacity: 3,300 lbs.



Li 24

24V end-rider pallet truck
ECR 327/336 | ECR M27 – ECR M36
travel distance: medium / long
capacity: 6,000 / 8,000 lbs.



24V ride-on pallet truck
ERE 125/225/225DP
travel distance: medium / long
capacity: 5,500 lbs.



24V center control rider
ECE 227(HP)XL / ECE 236(HP)XL
ECE M27 – M36
capacity: 6,000 / 8,000 lbs.



manual pallet truck
capacity: 4,850 lbs.

Pantograph Reach



Li 36
2/1

36V pantograph single / deep reach trucks
ETR 214-316d
max. fork height: 450 inches
capacity: 3,000–4,500 lbs.



Li 36
2/1

36V wide chassis sit/stand pantograph
reach truck
ETR 420-416d
max. fork height: 550 inches
capacity: 3,500–4,500 lbs.