




**Side shifting fork positioner for PD6 Series  
(FD60-4/4L, FD70-4/4L & FD80-4)**

Independent control will come standard with 5 spool valve & housing



**PD6 Series**

**ATTACHMENTS**

**FORK POSITIONER SPECIFICATIONS**

**Main Specifications**

Applicable Model		FD60-4	FD70-4	FD80-4
Load Capacity		6.0 Ton	7.0 Ton	8.0 Ton
Mast Type		VM		
Load Center	in (mm)	24 (600)		
Attachment Code		FSS425	FSS426	FSS435
Attachment Width	(WA) in (mm)	75.2 (1910)		79.3 (2015)
Fork Positioning Range	(O) in (mm)	14.2 (360) - 66.5 (1,690)		16.9 (430) - 70.5 (1,790)
Side Shift Range (LR)	in (mm)	5.9 (150)		
Overall Length	(L) in (mm)	200.8 (5100)	203.5 (5170)	211.8 (5380)
Fork Size	(F) in (mm)	* 54.0 (1,370)		48.0 (1220)
	(b) in (mm)	5.9 (150)		7.0 (180)
	(t) in (mm)	2.4 (60)	2.7 (70)	2.9 (75)

\* 48" (1200mm) forks are not available for 6-7 ton models.

**LOAD CAPACITY CHART WITH SIDE SHIFTING FORK POSITIONER**

Model	Mast Model	Load Capacity lbs. (kgs)
FD60-4/FD60-4L	VM300	10805 (4900)
	VM330	
	VM350	
	VM400	
	VM450	
	VM500	
	VM550	
FD70-4/FD70-4L	VM300	12790 (5800)
	VM330	
	VM350	
	VM400	
	VM450	
	VM500	
	VM550	
FD80-4	VM300	14995 (6800)
	VM330	
	VM350	
	VM400	
	VM450	
	VM500	
	VM550	
	VM600	12570 (5700)

UniCarriers® is a registered trademark of UniCarriers Corporation. UniCarriers Americas Corporation reserves the right to make product changes relating to colors, equipment, specifications or available options without notice. For more information, contact your UniCarriers representative.

